```
state 0
	$accept : _E $end
	Prefix : _    (4)

	Ftok  shift 4
	Vtok  shift 3
	.  reduce 4

	E  goto 1
	Prefix  goto 2

state 1
	$accept :  E_$end

	$end  accept
	.  error


state 2
	E :  Prefix_LPARENtok E RPARENtok

	LPARENtok  shift 5
	.  error


state 3
	E :  Vtok_Tail
	Tail : _    (6)

	PLUStok  shift 7
	.  reduce 6

	Tail  goto 6

state 4
	Prefix :  Ftok_    (3)

	.  reduce 3


state 5
	E :  Prefix LPARENtok_E RPARENtok
	Prefix : _    (4)

	Ftok  shift 4
	Vtok  shift 3
	.  reduce 4

	E  goto 8
	Prefix  goto 2

state 6
	E :  Vtok Tail_    (2)

	.  reduce 2


state 7
	Tail :  PLUStok_Vtok

	Vtok  shift 9
	.  error

state 8
	E :  Prefix LPARENtok E_RPARENtok

	RPARENtok  shift 10
	.  error


state 9
	Tail :  PLUStok Vtok_    (5)

	.  reduce 5


state 10
	E :  Prefix LPARENtok E RPARENtok_    (1)

	.  reduce 1


8/300 terminals, 3/300 nonterminals
7/600 grammar rules, 11/1000 states
0 shift/reduce, 0 reduce/reduce conflicts reported
5/350 working sets used
memory: states,etc. 49/24000, parser 4/12000
8/600 distinct lookahead sets
3 extra closures
8 shift entries, 1 exceptions
4 goto entries
1 entries saved by goto default
Optimizer space used: input 23/24000, output 13/12000
13 table entries, 3 zero
maximum spread: 261, maximum offset: 261
```